

		RIVER 3 Plus
Genral	Product Name	RIVER 3 Plus
	Capacity	286Wh/89600mAh
	Dimension	234 x 231 x 146 mm 9.2 x 9.1 x 5.8 inches
	Net. Weight	4.7 kg/10.4 lb
Battery	Battery Chemistry	LFP (LiFePO4)
	Cycle Life	3000 cycles to 80% capacity
Output	AC Output	3 ports, 230V~50Hz, 600W total (Surge 1200W, X-Boost 1200W)
	USB-A Output	2 ports, 5V=2.4A, 12W Max per port, total 24W
	USB-C Output	1 port, 5/9/12/15V=3A Max, 20V=5A Max,100W Max
	Car Output	1 port, 12.6V, 10A, 126W
	Wireless	✕
Input	AC Recharge	200~240V, 3A Max, 50/60Hz, 360W 0-100% in 60 min
	Solar Recharge	11~55V, 13A Max, 220W, 0-100% in 1.5 hr (45W input 0-100% in 7.3 hrs) (60W input 0-100% in 5.5 hrs) (110W input 0-100% in 3 hrs)
	Car Recharge	11~55V, 8A Max, 220W Max 0-100% in 3.3 hr
	Generator Recharge	200~240V, 3A Max, 50/60Hz, 360W 0-100% in 60 min
	USB-C Recahrge	✕
Others	UPS	<10ms
	EB	Only support 1 extra battery, 2 models to choose: EB300 (286Wh); EB600 (572Wh)
	APP	Wi-Fi &Bluetooth
	Noise	30db

	Waterproof	IP54 only for battery pack, not the whole package
	Warranty	5 years
	EB Interface	
Rapid	Capacity	×
	Dimension	×
	Net. Weight	×
	Input/output	×
Environment Temperature	Optimal Operating Temperature	20°C-30°C (68°F-86°F)
	Charge Temperature	0°C-45°C (32°F-113°F)
	Discharge Temperature	-10°C-45°C (14°F-113°F)
	Storage Temperature	20°C-30°C (68°F-86°F)
Operating Altitude		≤2000 m
What's in the box		RIVER 3 Plus AC Charging Cable Car Charging Cable USB-B to USB-A UPS Communication Cable Quick Start Guide and warranty